

**National Type Evaluation Program  
Certificate of Conformance  
for Weighing and Measuring Devices**

**For:**

Weighing/Load Receiving Element  
Models: SB Series  
Capacity: 30 lb (15 kg) to 500 lb (220 kg)  
 $e_{min}$ : 0.005 lb (0.025 kg)  
 $n_{max}$ : See Below  
Platform: See Below  
  
Accuracy Class: III

**Submitted by:**

A & D Engineering, Inc.  
1555 McCandless Drive  
Milpitas, CA 95035  
Tel: (408) 263-5333  
Fax: (408) 263-0119  
Contact: Jesus Zapien

**Standard Features and Options**

Stainless steel weighing pan

Base unit material: SB-15K10: Stainless steel

SB-60K11, SB-100K12, SB200K12: Aluminum alloy die casting

Models	Capacity	$e_{min}$	$n_{max}$	Platform (mm)
SB-15K10	30 lb (15 kg)	0.005 lb (0.0025 kg)	6 000	250 x 250
SB-60K11	150 lb (60 kg)	0.05 lb (0.02 kg)	3 000	330 x 424
SB-100K12	200 lb (100 kg)	0.05 lb (0.025 kg)	4 000	390 x 530
SB-200K12	500 lb (220 kg)	0.1 lb (0.044 kg)	5 000	390 x 530

**Load Cells:**


A&D Load Cell Models: LC-131-15K, LC-132-60K, LC-133-100K, LC-133-200K (non-NTEP)

Temperature Range: -10 °C to 40 °C (14 °F to 104 °F)

This device was evaluated under the National Type Evaluation Program (NTEP) and was found to comply with the applicable technical requirements of Handbook 44, "Specifications, Tolerances, and Other Technical Requirements for Weighing and Measuring Devices." Evaluation results and device characteristics necessary for inspection and use in commerce are on the following pages.



Ronald D. Murdock  
Chairman, NCWM, Inc.



Louis E. Straub  
Chairman, National Type Evaluation Program Committee  
Issue date: May 28, 2002

Note: The National Conference on Weights and Measures does not "approve", "recommend", or "endorse" any proprietary product or material, either as a single item or as a class or group. Results shall not be used in advertising or sales promotion to indicate explicit or implicit endorsement of the product or material by the NCWM.